

Data Sheet : EVICOM GX4/770

Description : Clear, flexible extrusion compound
Application : Extruded profiles and cable sheathing
Surface finish : Gloss
Specification : BS 7655:2000 Types T12/TM2

Property	Standard	Method	Unit	Value
BS Softness	BS 2782	365A	-	46
Shore A Hardness (15 sec)	BS 2782	365B	-	75
Density	BS 2782	620A	g/cc	1.23
Tensile strength	BS 2782	320A	N/mm ²	23.0
Elongation	BS 2782	320A	%	400
Cold flex	BS 2782	150B	°C	-20
Cold bend	BS 2782	151A	°C	-45

**For prompt attention, contact our
Customer Service Office :**

INEOS Compounds Ltd
Chester Rd, Helsby
Warrington, Cheshire
WA6 0DF

Direct Telephone Lines :
Rigid Products +44 (01928) 762713/15
Flexible Products +44 (01928) 762712/16/17
or Fax us FREE on (0800) 220613
or from outside UK +44 (01928) 725101

All data in this publication have been obtained from laboratory tests on representative samples, however they are for general guidance only and must not be used as the basis of a specification.

Information contained in this publication (and otherwise supplied to users) is based on our general experience & is given in good faith, but we are unable to accept responsibility in respect of factors which are outside our knowledge or control.

Users should consult the appropriate Evicom Safety Data Sheet and may obtain further information from the INEOS Compounds Customer Service Office.